



# GLIDE SERIES

Illuminate indoor spaces with elegance and efficiency using the GLIDE Ceiling Light. Crafted from high-quality extruded aluminum, this suspended lighting solution offers direct, wide-beam distribution with a choice of opal or MPO optics for tailored ambiance. With LED wattage options ranging from 11W to 44W and color temperatures available in 3000K, 4000K, and 5700K, GLIDE delivers an adaptable, high-performance lighting experience. Designed for durability, it operates within 0-45°C and 10-60% humidity, featuring a robust IP20 rating, overvoltage, and short-circuit protection. Ideal for modern interiors, GLIDE is available in sleek black or white finishes and comes in multiple lengths to fit diverse design needs.

## Technical Info

<b>L</b>	591mm	1176mm	1761mm	2346mm
<b>W</b>	50mm	50mm	50mm	50mm
<b>H</b>	70mm	70mm	70mm	70mm

### ENVIRONMENT

Indoor

### MOUNTING

Ceiling  
Suspended

### LAMP DESCRIPTION

Lamp Type : LED  
 Wattage : 11/22/33/44 W  
 CCT : 3000/4000/5700 K  
 Luminaire Efficacy (Opal) : 90 lm/W  
 Luminaire Efficacy (MPO) : 80 lm/W  
 CRI : >80/90  
 Chromaticity Tolerance (SDCM) : 3/5  
 Lumen Maintenance : 60,000 h (L70/B10)

